



UM397

Bench

Leman

By Compagnies Desrués © BENITO




Controlled logging



Grey Casting



Inclusive Product



Hardwood



M10 bolts fixing




LEMAN design Bench, overall dimensions (length x height x depth) 2300x830x600 mm, manufactured with ductile iron legs (treated with the Ferrus triple-layer protective process for iron, guaranteeing optimal corrosion resistance). Finished with epoxy primer and gray polyester powder coating, and tropical wood planks with a natural finish (treated with Lignus triple-layer coating, a fungicidal, insecticidal, and water-repellent protector). Stainless steel screws. Prepared for anchoring with M10 expansion bolts depending on the surface and project.

Optional extras not included: Customizable branding with 74x35 mm aluminum plate. Without armrests.

Ductile Iron treated with FERRUS: iron protection process that ensures optimal corrosion resistance. The Ferrus treatment consists of three layers applied after cleaning all dirt and impurities using shot blasting, involving an electrolytic bath followed by an epoxy primer and a final coating of polyester powder paint. Forged black colour

Hardwood treated with LIGNUS: Wood from responsible forestry. Density greater than 930kg/m³, at 12% humidity, treated with a triple-layer LIGNUS coating, fungicide, insecticide, and water-repellent that provides protection against moisture penetration. Final finish with a layer of natural pigment in a satin finish, which provides additional protection against UV rays, the main cause of deterioration in this type of material.



Ref.	A	B	H	H1
UM397	2300	600	830	420
UM397B	2300	545	450	
UM397S	650	600	830	420

Leman
UM397S



Leman
UM397B



